



Cabled Shell

Finished chest measurements: 37
(41,44,49,55)"
Gauge: 3.5 sts / 5 rows = 1" Keyplate 4,
Bulky: Tension 8
Materials: Chunky weight yarn: 440 500,
540, 600, 700 yards / 12, 13, 14, 16, 17 ozs.
(We used Rowan Cotton Rope yarn 50
gm/1/75 ozs. 63 yards).



1. E wrap cast on 66(72,78,86,94) stitches. Row counter at zeros. Knit 2 rows. The cable will be made on the center 6 sts of the knitting.
2. Transfer the next st on both sides of the center cable sts to adjacent needle.
3. Place empty needles in nwp. (You should have 6 sts between the needles in nwp).
4. Knit 1 row. Begin cable pattern on center 6 sts.
5. Remove the first 2 sts onto a 2 prong transfer tool and hook onto adjacent empty needle to hold.
6. Transfer the middle 2 sts with a 2 prong transfer tool to adjacent 2 empty sts.

7. Cross the 2 sts on first 2 prong tool to middle 2 empty needles. Make sure the 2 sts on either side of the center 6 cable sts are in nwp.
 8. Place the 4 sts just crossed to fwp to make knitting easier. Knit 4 rows.
 9. Remove the last 2 sts onto a 2 prong transfer tool and hook onto adjacent empty needle to hold.
 10. Repeat steps 6 through 8.
 11. Repeat steps 5 through 10 to rc = 60.
- Continuing in cable pat, begin armhole decreases:
12. Bind off 2(3,4,5,6) sts at beg of next 2 rows.
 13. Transfer 3rd st on each end to next st in. Transfer end sts so there are no empty needles in work. Knit 2 rows.
 14. Repeat last step 2 times more. Knit to rc = 104(108,116,118,120).
 15. Bind off all sts.
- Front: Work same as for back.
Block pieces.

Sew 2.5(3,3,4,4.5)" of top edge on each side for shoulder, leaving remaining neck edge open. Sew side seam. Weave in ends.

If you don't like the curled edges, you can work a row or 2 of crochet around edges.

This pattern is intended for personal use only. This pattern is copyrighted and cannot to be sold without permission.

When reproduced, must acknowledge KangaMooKnits.com as author.